


SAP E & C SPLIT RANGE CONTROL TRAINER
(PRODUCT CODE: SAP - 44)



SPLIT RANGE CONTROL TRAINER (SAP - 44)

The **Split Range Control Trainer (SAP - 44)** is highly flexible and modular system for studying of Split Range Control Loops (Pressure Control Loop / Level Control Loop) optional in industrial processes.

Technical Specification:

No.	Item Name	Technical Specifications
1	Sump tank-	Material: Polypropylene 5 mm thick, Capacity: 30 liters, Dimension: 12"(L) × 24"(W) × 16" (H).
2	Level Tank-	Material: P.P. 5mm thick, Dimension: 150(L) mm× 150(W) mm× 600(H) mm
3	Centrifugal Pump-	1 H.P., 1ϕ 230 V AC supply, Surface mounting.
4	Pressure vessel-	Shape: Cylindrical, Material: SS 304,(With pressure Loop) Diameter: 150 mm, Length: 300 mm, Capacity: 15 Kg/cm ² , with ½" BSP connection For Pressure Gauge, Pressure Transmitter, Inlet & Drain facility
5	Piping-	1" Class B GI with 1" SS ball valves.
6	Level Transmitter-(With level Loop)	Input: 0-400 /0-500 mm, Output: 4-20 mA, supply: 24 V DC, 100 mA. Type: 2-wire capacitance type, Mounting: Top 2" screwed connection.
7	Pressure Transmitter-(With Pressure Loop)	Input: 0-2.5 Kg/cm ² / 0-4 Kg/cm ² , Output: 4-20 mA, supply: 24 V DC, 50 mA. Type: 2-wire Piezoresistive type, Medium: Water Pressure. Mounting: Top ½" BSP connection.
8	Pneumatic Control Valve-	2 no. Size: 1", Characteristics: Equal percentage. Type: Two way Globe type with valve Positioner (Air to Close) & two way Globe type with valve Positioner (Air to Open), Cv: 9 US GPM, with diaphragm actuator. Flange connection: PCD: 80 mm, ID: 26 mm, OD: 110 mm. Positioner Action: 0.2 to 1.0 Kg/cm (Direct Action / Reverse Action) Pneumatic Input Signal: 0.2 to 1.0 Kg/cm ²
9	E/P Converter -	Input: 4-20 mA, Output: 3-15 psi, Connection ¼" NPT / BSP

SAP E & C SPLIT RANGE CONTROL TRAINER
(PRODUCT CODE: SAP - 44)



10	Rotameter	1 No. Range : 0-2000 LPH , Glass Tube Type/ Acrylic body , Bob Material SS 304, Connection 1" Mounting Inlet Bottom, Outlet Top
11	A.F.R. / F.R.L. Unit-	0-10 Kg/cm ² with pressure gauge, Connection ¼" NPT / BSP.
12	Power Supply-	24 V DC, 1.5 A/ 3A, Size: 48mm×126mm×68mm.
13	Electronic PID Controller-	1 No., Single input PID with Serial Interface (ASCII Protocol) USB / Ethernet / RS 485 / RS232, Cut Out Size; 92×92×144mm, Input: 4-20 mA, Output: 4-20 mA, Display: Dual for PV & SP, Bar graph display for Output & deviation, Hi-Low alarm annunciations.
14	Electrical Control Panel-	MS Powder coated panel with switches, indicator, Test Points, controller on front facia, UK 2.5 Terminal connectors mounted on DIN rail channel, Use of 1sq mm multistand wire with proper insulated lugs, Ferruling & neat wire dressing & clamping wires & power cables are seated through 1"×1" PVC cable tray. Dimension: 1ft (L) ×1ft (W) ×1ft (H).
15	SCADA Application Software (Optional)-	SCADA S/W, And PID mode, Auto/Manual Tuning of PID, Data Storage, Off Line analysis, Online Data Acquisition, Simulation and Printing Of data in Graphical and tabular form. Interactive Graphical User Interface (GUI) includes.
16	Air Compressor (Optional)-	Tank capacity: 30 Liters, Discharge: 2 CFM, Motor: ½ H.P. 1φ 230 VAC Operated, Working Pressure: 3-4 Kg/cm ²
17	Computer (Optional)-	PC with colour monitor: 15", PC Pentium Dual Core, With 2 serial communication ports, 80 GB HDD, 512MB RAM, Floppy Drive.

Range of experiments-

- ❖ Feedback control: - Pressure/Level.
- ❖ Split Range control: - Pressure/Level.
- ❖ Study of SCADA Application Software/ Computerized Control of Split Range Control System.

Process Equipments-

- ❖ A sump tank and transparent acrylic tank (secondary) containing water.
- ❖ A control system to study split range control (Level/Pressure).
- ❖ Electrical control panel along with PC Interface module.

Features-

- ❖ Compact Ergonomic Design.
- ❖ User Friendly, Self Explanatory Systems.
- ❖ Leak proof Safety Measures, sturdy piping.
- ❖ Enhanced Electrical Safety Considerations.
- ❖ Training Manuals, Mimic Charts for Operation Ease.
- ❖ System Frame with Caster Wheel Arrangement for ease in movement.
- ❖ M.S. powder coated cubical plant with standard Instrument Mountings.
- ❖ Inbuilt Safety Measures to avoid improper usage.
- ❖ SCADA Application software connectivity for analysis of Split Range Control Trainer.

SAP E & C SPLIT RANGE CONTROL TRAINER
(PRODUCT CODE: SAP - 44)



System Dimension: 6 Ft. (L) X 2.5 Ft. (W) X 5.5 Ft. (H)

Services Required:

- ❖ Electric supply 1 ϕ 230VAC, 50Hz.
- ❖ Water Supply and Drain Arrangement.
- ❖ Clean, dry, compressed air supply at 2.1 kg /cm².

Note:

All descriptive matter and illustrations are intended to give only a general idea of the equipment detailed specifications may be altered at the company's discretion without any notice.

Manufactured/Marketed By

SAP ENGINEERS & CONSULTANTS



Regd. Off. : Shop No. 26-27,'Srushti', Survey No.82, Near Guru Ganesh Nagar,
Eklavya College Road (D.P.Road), Kothrud, Pune - 411 038
Telephone : (020) 2538 4737
Mobile : 94220 88946, 95524 75082
Fax : (020) 2538 3544
Email : pravinsdeode@vsnl.net, sapengineerspune@gmail.com
Website : www.sapengineers.com / www.sapengineers.co.in

3/3_2