SAP E & C INTERACTING & NON-INTERACTING SYSTEM (SAP-77)





Technical Specification:-

No.	Item Name	Technical Specifications
1	Rotameter-	1 No., Range: 40-400 LPH, Glass tube type/acrylic body, Bob Material: SS 304
		Connection: 1", Mounting: Inlet- Bottom, Outlet- Top.
2	Process Tank-	3-Nos., Dimensions: 6"X6"X12"stainless steel/acrylic/P.P.5mm thick ,with
		graduated scale in mm.
3	Supply Tank-	Dimensions: 1'X 1'X 1', Material: stainless steel1.5mmthick/acrylic/P.P. 5mm
		thick,
4	Centrifugal Pump	1/2"H.P. 230V AC Supply, Surface mounting.

Page: 1 of 2

SAP E & C INTERACTING & NON-INTERACTING SYSTEM (SAP-77)



Features-

- Compact Ergonomic Design.
- User Friendly, Self Explanatory Systems.
- * Robust Construction.
- Enhanced Electrical Safety Considerations.
- Training Manuals mimic Charts for Operation Ease.
- Inbuilt Safety Measures to avoid improper usage.
- Caster wheel mounted movable frame

Range of Experiments:

- ❖ Study Of dynamic response of interacting & non interacting system
- Study Of step response of first order systems arranged in non interacting & interacting mode
- Study of step response of single capacity system.

Services Required-

Electric Supply of 1φ 230 VAC motor.

Note-

All descriptive matter and illustrations are intended to give only a general idea of the equipment Detailed specifications may be altered at the company's discretion without any notice.



Page: 2 of 2