
# SAP E & C TEST RIG FOR SPRING BACK ACTION (PRODUCT CODE: SAP – 86)





The **Test Rig for Spring Back Action (SAP - 86)** is useful for study of Elasticity of metallic Sheets. The Setup is useful for studying the tensile-Physical / Elastic properties of Materials.

## **Technical Specification:**-

No.	Item Name	Technical Specifications
1	Oil Hydraulic power	MS Powder Coated Oil Tank, Capacity: 25 Liters., with
	pack-	Oil Level Indicator, Gear Pump: 3 LPM, with Strainer Filter.
		70 bar, Breather, Oil filter & suction,
		3 Phase, ½ HP, 415 AC Electric Motor with DOL starter
2	Force Applying	Single Acting cylinder, Foot Mounting, Stroke Length
	Mechanism-	
3	Block Manifold-	¼", 4 ways
4	Pressure Gauges-	3 nos., 100 Kg/cm <sup>2</sup> , Dial Size: 50 mm, Glycerin Filled.

# SAP E & C TEST RIG FOR SPRING BACK ACTION (PRODUCT CODE: SAP – 86)



5	Deformation/Strain	Least Count: 0.01mm/ 100micron, Output: mm of Displacement
	Indicator-	
6	<b>Deformation / Strain</b>	LVDT-Input ±10mm, 230 V AC
	Measuring	
	Mechanism-	
7	Stress Applying	V Shaped Mechanism
	Mechanism-	
8	<b>Direction Controlling</b>	4 / 3 Direction Control Valve Hand Lever Operated.
	Valve-	
9	M.S. powder coated plant with standard Instrument Mountings.	

### Range of Experiments-

- Study of Stress & Strain Measurement.
- Study of Physical Properties of Materials.
- Study of Elasticity, Spring Back Action etc.

#### Features: -

- Compact Ergonomic Design.
- User Friendly, Self Explanatory Systems.
- Robust Construction.
- Enhanced Electrical Safety Considerations.
- Training Manuals, Mimic Charts for Operation Ease.
- Inbuilt Safety Measures to avoid improper usage.
- M.S. powder coated plant with standard Instrument Mountings.

#### **Services Required-**

Electric Supply of 1φ 230 VAC, 50Hz

### Note-

All descriptive matter and illustrations are intended to give only a general idea of the equipment Detailed specifications may be altered at the company's discretion without any notice.

